

V7 D22W11

Specifications

Panel Size	22" (559 mm)
Aspect Ratio	16:10 (~ 474 x 296 mm)
Recommended Resolution	1680 x 1050 WSXGA
Pixel Pitch	0.282 mm
Colours max.	16.2 Mio
Brightness typ.	300 cd/m ²
Contrast Ratio typ.	1000:1
Viewing Angle H/V	160°/160°
Response Time typ.	5 ms
Surface Treatment	Anti-glare, Hard-coating
Audio System	Audio lin in and speaker out
Features	Speakers (2x 1.5 W), Kensington® Security Port, internal power supply, black design
Adjustment	Auto-Setup, Clock, Phase, H/V-Position, Brightness, Contrast Ratio, Sharpness, Color, OSD Position, Language, Audio, Recall etc.
Frequency at Resolution	640 x 480 @ 75 Hz 800 x 600 @ 75 Hz 1024 x 768 @ 75 Hz 1280 x 1024 @ 75 Hz 1440 x 900 @ 75 Hz 1680 x 1050 @ 60 Hz
Horizontal Frequency	31.5 - 83 kHz
Vertical Frequency	56 - 76 Hz
Video Bandwidth	140 Mhz
Input Signal	RGB analog
Input Terminal	15pin D-Sub
Plug & Play	VESA DDC2B/CI
Power Management	ENERGY STAR®
Power Consumption On/Off	55/1 Watt max.
Power Requirements	AC 100 - 240V, 50/60 Hz
Dimensions WxHxD	
with stand	510 x 424 x 203 mm
without stand	510 x 415 x 68 mm
packaging	569 x 480 x 138 mm
Wallmountable	100 mm x 100 mm
Weight without/with stand	4.9 kg
incl. packaging	6.7 kg
Tilt	0° - 20°
Operating/Storage Temperature	5-40°/-20-60°C, Humidity: 20-80%/5-80%
Certifications & Standards	CE, TUV/GS, cUL, CB, CCC, FCC-B, TCO '03, ISO 13406-2
Supplied Accessories	multilingual user manual on CD-Rom, quick start guide, 1.8 m power cable, 1.8 m VGA cable, audio cable
Pixel Criteria	bright <= 4, dark <= 4, total <= 9
Service	3 years on-site
EAN Code	4038489004581

