

V7 R19W11

Entertainment Line

Specifications

Panel Size	19" (483 mm)
Aspect Ratio	16:10 (~ 408 x 255 mm)
Panel Specification	Wide Aspect Innolux Panel, TN
Recommended Resolution	1440 x 900 Super Wide Viewing Angle
Colours max.	16.2 Mio
Brightness typ.	300 cd/m ²
Contrast Ratio typ.	700:1
Viewing Angle H/V	150°/130°
Response Time typ.	5 ms
Features	Speakers (2x1W), Kensington® Security Port, embedded power supply, silver-black design
Adjustment	Auto-Setup, Brightness, Contrast Ratio, Clock, Phase, H/V-Position, Sharpness, Color, OSD Position, Language, Volume, Recall etc.
Frequency at Resolution	640 x 480 @ 75 Hz 800 x 600 @ 75 Hz 1024 x 768 @ 75 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz
Horizontal Frequency	30 - 80 kHz
Vertical Frequency	56 - 75 Hz
Video Bandwidth	135 Mhz
Input Signal	RGB analog
Input Terminal	15pin D-Sub
Plug & Play	VESA DDC1/2B
Power Management	VESA DPMS, ENERGY STAR
Power Consumption On/Off	45/1 Watt max.
Power Requirements	AC 100 - 240V, 50/60 Hz
Dimensions WxHxD	
with stand	449 x 382 x 191 mm
without stand	449 x 353 x 60 mm
packaging	526 x 393 x 124 mm
Weight without/with stand	4.7 kg
incl. packaging	5.7 kg
Tilt	-5° - 20°
Storage/Operating Temperature	-20-60/0-40°C, Humidity: 10-90/20-80%
Wallmountable	VESA 100 x 100 mm
Certifications & Standards	CE, TÜV/GS, TCO '03, ISO 13406-2
Supplied Accessories	14 language manual CD-Rom, power cable, VGA cable, audio cable
Pixel Criteria	bright <= 3, dark <= 3, total <= 7
Service	3 years on-site
EAN Code	4038489004130

